

Technical Information

Hardware Descriptions

Back to Back Knob

A variety of handles are available for the frameless doors. Our standard supply is the back to back mushroom door knob.

Y-Black Nylon Catch

A Y catch is fitted to the opening door to keep it in the open position and prevent it from slamming closed in windy conditions.

Middle hinge / with pull handle

Our doors can be used up to heights of 3000mm, to create more stability in windy conditions, we are able to fix a middle hinge to the doors. Each middle hinge in line with the Roller and Guide hinge is fitted with a pull handle to assist in closing.

Locking Plate

The locking plate locks the opening door into position when closed.

Pivot Hinge

The pivot hinges are placed into the side track extrusion and form the base for the direction the doors fold towards.

Roller Hinge

The roller hinge is placed in the top track, our stainless steel bearings allow for a smooth opening and closing of our “top hung” system doors.

Guide Hinge

The guide hinge is placed on the bottom section of the doors, the guides roll in the bottom track preventing the doors from swinging out.

Locking Hinge with Pull handle

The pull handle on the locking hinge helps pull the doors closed, enabling it to lock easier.

Locking Hinge

Our doors are hinged together to make it a folding system, not stacking. The Locking Hinge is placed on the doors folding out, and lock into place in the top and bottom extrusion when closed.

Locking Extension Handle

For doors higher than 2300mm, the extension handle is used to unlock and lock the locking pin.

Bubble Seal

Each door is fitted with a UV resistant bubble seal to assist with the water resistance of our doors.

Should you require any further information, please do not hesitate to contact us.

www.galaxyshowers.co.za

www.clearviewfoldingdoors.co.za